

96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: testing@govmark.com

Page 1

Received: 02/07/2018 | Completed: 02/16/2018 | Letter: W4 RG | P.O.#: Test Report #: 3-24458-4-

Client's Style: 2480 Cura. Date of Mfg.: 30-01-2018. Composition: 100% Post-Consumer Recycled Polyester. Weight: 420 g/lm.

Identification | Color #: 60111-Black. Product End Use: Upholstery.

Tested For: Bente Ellingsoe, Quality Department

Key Test: ASTM D 4034/ACT

150

Gabriel A/S Hjulmagervej 55

Tel: 011-45-9630-3100

Ext:

DK-9000 Aalborg, Denmark

Fax: 011-45-9811-6125

Test Category: Seam Slippage

Specifier: ACT

LE 2015; V 08/15 PC: 8H

dl/SM

NTR 6/16

TEST PERFORMED: ASTM D 4034 - Standard Test Method for Resistance to Yarn Slippage at the Sewn Seam in Woven Upholstery Fabrics - Plain, Tufted, or Flocked --

As cited by the ACT Voluntary Performance Guidelines (January 2015)

PRODUCT CATEGORY: Upholstery

ACCEPTANCE CRITERIA: 25 lbf minimum average for warp and weft

SEAM CONSTRUCTION:

Seam Allowance: 0.5"

Seam Type:

Thread Type:

301 Lockstitch 100% Nylon Bonded Monocord;

Needle Thread size 8/Bobbin Thread Size 5

Needle: Size 22 Ball Point

Stitches/Inch: 7 ± 0.5

RESULTS:

Specimen results reported to the nearest 0.5 lb force (lbf)

/71 CV

Average reported to the nearest 0.5 lb force (lbf)

	Specimen #		(lbf)	
Warp Yarn Slippage:	1		119.0	SB
(seamed in warp direction)	2		111.5	SB
	3		113.0	SB
	4		114.5	SB
	5		112.0	SB
	A:	vg:	114.0	
Weft Yarn Slippage:	6		104.5	SB
(seamed in weft direction)				
	8		117.5	SB
	9		103.0	SB
	10		112.0	SB
	A	vg:	110.5	
		. 9.	110.0	

ABBREVIATIONS WHICH MAY BE USED:

SS = Seam Slippage

SB = Seam break before 1/4" slippage

FB = Fabric break before 1/4" slippage

FBS = Fabric break at Seam before 1/4" slippage

(Page 1 of 2)



96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: testing@govmark.com

Page 2

Received:02/0	07/2018 Completed: 02/16/2018	Letter: W4	RG	P.O.#:	Test Report #:	3-24	1458-4-
Client's Identification	Style: 2480 Cura. Date of Mfg Color #: 60111-Black. Product			tion: 100% Post-Consu	mer Recycled Polyeste	er. Weight: 420	g/lm.
Tested For: I	Bente Ellingsoe, Quality Dep	artment		Key Test: A	ASTM D 4034/ACT		150
(Gabriel A/S						
I	Hjulmagervej 55			Tel: ()11-45-9630-3100	Ext:	
ī	DK-9000 Aalborg, Denmark			Fax: ()11-45-9811-6125		

REMARKS: None.

CONCLUSION: Based on the above Results and Acceptance Criteria, the item tested:

[x] Complies; [] Does not comply

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

AUTHORIZED SIGNATURE

GOVMARK /jb Ipm Phyllis Pettit FEB 2 6 2018

(Page 2 of 2)